

R 914 Compact G6.1-D (781858-2) (R 914 K-S 1511)

Basic machine

R 914 Compact G6.1-D
Power Pack EU Stage V
Centralized lubrication system (automatic)
Standard packaging

Undercarriage

Undercarriage S, track gauge 2000 mm
Dozer and stabilizer blade 2740 mm via mini-joystick
B4 chains 700 mm triple grouser track pads 46 links
Chain guide 1 piece
Undercarriage storage compartment
Steps wide

Uppercarriage

Hydraulic oil, Liebherr hydraulic HVI (-20 to +40 °C)
Tank refilling pump fuel
Electric socket on uppercarriage (24 V)
Counterweight standard 2.8 t
Right hand side view monitoring camera
Tool set including storage case

Cab

Radio Comfort
Operator seat Comfort
2" seat belt with retractor
Auxiliary heater programmable
LiDAT Hard and Software; consider the LiDAT-license customer terms of a license
Retractable laminated two-piece windscreen
Bottom windscreen wiper
Flashing beacon on cabin, LED, 1 piece
Medium pressure circuit via mini-joystick
High pressure circuit with Tool Control via mini-joystick
Handrests elevated for Joysticks
Short key buttons on joystick configurable
Implantation of commands is validated

Equipment

Mono boom 4.60 m
Pipe fracture safety valves for boom cylinders
Pipe fracture safety valve for stick cylinder
Stick 2.45 m
Centralized lubrication extended for connecting link

Packs

Pack Premium LED+ Elite
Pack Surround LED+